Printing date 01/22/2016 Reviewed on 01/22/2016

# 1 Identification

- · Product identifier
- · Trade name: Pro-Poxy<sup>TM</sup> 300 Fast Part A
- · Article number: 87-140177A
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Unitex® 3101 Gardner

Kansas city, MO 64120

Tel: (800) 821-5846 Fax: (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

# 2 Hazard(s) identification

· Classification of the substance or mixture

Eye Irrit. 2A H319 Causes serious eye irritation.

Carc. 2 H351 Suspected of causing cancer.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

*Talc* (*Mg3H2*(*SiO3*)4)

· Hazard statements

Causes serious eye irritation.

Suspected of causing cancer.

· Precautionary statements

Wear eye protection / face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 1Reactivity = 0


(Contd. on page 2)

Printing date 01/22/2016 Reviewed on 01/22/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part A

· HMIS-ratings (scale 0 - 4)

(Contd. of page 1)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

14807-96-6 Talc (Mg3H2(SiO3)4)

≤ 10%

· Additional information: For the wording of the listed risk phrases refer to section 16.

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

*Immediately remove any clothing soiled by the product.* 

In the event of persistent symptoms recieve medical treatment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Seek immediate medical advice.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 01/22/2016 Reviewed on 01/22/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part A

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow product to reach sewage system or any water course.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- Requirements to be met by storerooms and receptacles: Store in a cool dry location.
- · Information about storage in one common storage facility: Store away from incompatible materials.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 4)

Printing date 01/22/2016 Reviewed on 01/22/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part A

(Contd. of page 3)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

0 D1 .	7	- 7			
9 Physical	and	$\boldsymbol{c}$	nomical	nro	nortios
) I II you ui	unu	$\boldsymbol{\sigma}$	<i>telliteat</i>	ייועי	permes

Information on basic physical and General Information	ononwow proportios		
Appearance:			
Form:	Liquid		
Color:	Liquid Clear		
Odor:	Mild		
Odor threshold:	Not determined.		
pH-value:	Not determined.		
	nor actermatea.		
Change in condition			
Melting point/Melting range:	Undetermined.		
Boiling point/Boiling range:	Undetermined.		
Flash point:	> 93 °C (> 199 °F)		
Flammability (solid, gaseous):	Not applicable.		
Ignition temperature:			
Decomposition temperature:	Not determined.		
Auto igniting:	Product is not selfigniting.		
Danger of explosion:	Product does not present an explosion hazard.		
Explosion limits:			
Lower:	Not determined.		
Upper:	Not determined.		
Vapor pressure:	Not determined.		
Density at 20 °C (68 °F):	1.2 g/cm³ (10.014 lbs/gal)		
Relative density	Not determined.		
Vapor density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with			
Water:	Not miscible or difficult to mix.		
Partition coefficient (n-octanol/wat	er): Not determined.		
Viscosity:			
<i>Dynamic at 20 °C (68 °F):</i>	1000000 mPas		
Kinematic:	Not determined.		

(Contd. on page 5)

Printing date 01/22/2016 Reviewed on 01/22/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part A

		(Contd. of page 4)
· Solvent content: Organic solvents:	0.0 %	
Solids content: · Other information	100.0 % No further relevant information available.	
· Volatile Organic Compounds:	Not determined	

### 10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

 Oral
 LD50
 5000 mg/kg (rat)

 Dermal
 LD50
 20000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye:

Strong irritant with the danger of severe eye injury.

Irritating effect.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· Carcinogenic categories

14807-96-6 Talc (Mg3H2(SiO3)4)

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 6)

Printing date 01/22/2016 Reviewed on 01/22/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part A

(Contd. of page 5)

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (Self-assessment): slightly hazardous for water
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- $\cdot$  **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to Federal, State, and Local regulations.

TINI NI 1	
· UN-Number · DOT, ADR, ADN, IATA · IMDG	Not Regulated UN3082
· UN proper shipping name · DOT, ADR, ADN, IATA · IMDG	Not Regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (epoxy resin), MARINE POLLUTANT
· Transport hazard class(es)	
· DOT, ADR, ADN, IATA · Class	Not Regulated
· IMDG	
· Class · Label	9 Miscellaneous dangerous substances and articles 9
· Packing group · DOT, ADR, IMDG, IATA	III

(Contd. on page 7)

Printing date 01/22/2016 Reviewed on 01/22/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part A

(Contd. of page 6) · Environmental hazards: · Marine pollutant: Symbol (fish and tree) · Special precautions for user · EMS Number: F-A,S-F· Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information:  $\cdot DOT$ · Remarks: Not Regulated for Transport.  $\cdot ADR$ · Remarks: Not Regulated for Transport. · U.S. Domestic Ground Shipments: Same as listed for Standard Shipments above. · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: Same as listed for Standard Shipments above. · Emergency Response Guide (ERG) Number: Not determine · UN "Model Regulation": Not Regulated

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to the State of California (Prop. 65) to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 8)

Printing date 01/22/2016 Reviewed on 01/22/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part A

(Contd. of page 7)

#### · TLV (Threshold Limit Value established by ACGIH)

14807-96-6 Talc (Mg3H2(SiO3)4)

*A4* 

#### · MAK (German Maximum Workplace Concentration)

14807-96-6 Talc (Mg3H2(SiO3)4)

*3B* 

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS08

GHS07

· Signal word Warning

### · Hazard-determining components of labeling:

*Talc* (*Mg3H2*(*SiO3*)4)

#### · Hazard statements

Causes serious eye irritation.

Suspected of causing cancer.

#### · Precautionary statements

*Wear eye protection / face protection.* 

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 01/22/2016 / 173
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 9)

Printing date 01/22/2016 Reviewed on 01/22/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part A

(Contd. of page 8)

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Carc. 2: Carcinogenicity, Hazard Category 2

Printing date 03/14/2016 Reviewed on 03/14/2016

# 1 Identification

- · Product identifier
- · Trade name: Pro-Poxy<sup>TM</sup> 300 Fast Part B
- · Article number: 87-140177B
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Unitex® 3101 Gardner

Kansas city, MO 64120

Tel: (800) 821-5846 Fax: (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

# 2 Hazard(s) identification

· Classification of the substance or mixture

Acute Tox. 4 H332 Harmful if inhaled.

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS05

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

*m-phenylenebis*(*methylamine*)

nonylphenol

cyclohex-1,2-ylenediamine

hexamethylenediamine

· Hazard statements

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

#### · Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
1477-55-0	m-phenylenebis(methylamine)	10-25%	
25154-52-3	nonylphenol	10-25%	
694-83-7	cyclohex-1,2-ylenediamine	≤10%	
	hexamethylenediamine	≤5%	
	tetramethylenediamine	≤1%	
156-87-6	3-aminopropan-1-ol	≤1%	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

*In the event of persistent symptoms recieve medical treatment.* 

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 3)

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

(Contd. of page 2)

- Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool dry location.
- · Information about storage in one common storage facility: Store away from incompatible materials.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

(Contd. of page 3)

#### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 1477-55-0 m-phenylenebis(methylamine)

REL Ceiling limit value: 0.1 mg/m<sup>3</sup>

Skin

TLV Ceiling limit value: 0.1 mg/m³

Skin

#### 124-09-4 hexamethylenediamine

TLV Long-term value: 2.3 mg/m³, 0.5 ppm

WEEL Long-term value: 1 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Grey

Odor: Distinctive

Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: Undetermined.

• Flash point: >94 °C (>201 °F)

(Contd. on page 5)

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

		(Contd. of page 4
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	370 °C (698 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	1.0 Vol %	
Upper:	$0.0\ Vol\ \%$	
Vapor pressure:	Not determined.	
Density at 20 °C (68 °F):	1.776 g/cm³ (14.821 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100.0 %	
Other information	No further relevant information available.	
Volatile Organic Compounds:	Not determined	

# 10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Reacts with acids, alkalis and oxidizing agents.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

 $(Contd.\ of\ page\ 5)$ 

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:				
1477-55-0 m-phenylenebis(methylamine)				
Oral	LD50	1040 mg/kg (rat)		
Inhalative	LC50/4 h	2.4 mg/l (rat)		
25154-52-3 nonylphenol				
Oral	LD50	1620 mg/kg (rat)		
124-09-4 hexamethylenediamine				
Oral	LD50	750 mg/kg (rat)		
Dermal	LD50	1110 mg/kg (rabbit)		

- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye: Strong caustic effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

(Contd. on page 7)

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

(Contd. of page 6)

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to Federal, State, and Local regulations.

### 14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

UN1760

· UN proper shipping name

 $\cdot$  DOT, IATA

 $\cdot ADR$ 

· IMDG

Corrosive liquids, n.o.s. (nonylphenol) 1760 Corrosive liquids, n.o.s. (nonylphenol)

CORROSIVE LIQUID, N.O.S. (nonylphenol), MARINE

**POLLUTANT** 

- · Transport hazard class(es)
- $\cdot DOT$



· Class · Label 8 Corrosive substances

· ADR, IMDG





· Class · Label 8 Corrosive substances

 $\cdot$  IATA



· Class

8 Corrosive substances

(Contd. on page 8)

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

	(Contd. of page
Label	8
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances
Marine pollutant:  Special marking (ADR):	nonylphenol Yes Symbol (fish and tree) Symbol (fish and tree)
Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Corrosive substances 80 F-A,S-B A
Stowage Category Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/ and the IBC Code	78 Not applicable.
Transport/Additional information:	
DOT Remarks:	Add "Marine Pollutant" to end of proper shipping name shipping in a bulk container (>119 gallons).
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
U.S. Domestic Ground Shipments: U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:	Same as listed for Standard Shipments above.  Same as listed for Standard Shipments above.
Emergency Response Guide (ERG) Number:	Not determine
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1760 CORROSIVE LIQUIDS, N.O.S., 8, III

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

25154-52-3 nonylphenol 10-25%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 9)

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

(Contd. of page 8)

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS08

GHS05

GHS07

· Signal word Danger

· Hazard-determining components of labeling:

 $m\hbox{-}phenylene bis (methylamine)$ 

nonylphenol

cyclohex-1,2-ylenediamine

hexamethylenediamine

· Hazard statements

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 10)

Printing date 03/14/2016 Reviewed on 03/14/2016

Trade name: Pro-Poxy<sup>TM</sup> 300 Fast - Part B

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 03/14/2016 / 239
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Repr. 2: Reproductive toxicity, Hazard Category 2

US