Tel: (800) 821-5846

Safety Data Sheet acc. to OSHA HCS

Printing date 03/17/2016 Reviewed on 03/17/2016

1 Identification

- · Product identifier
- · Trade name: Slow Set Bonding Agent Part A
- · Article number: 87-140440A
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Unitex® 3101 Gardner

Fax: (816) 483-3149 Kansas city, MO 64120

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2B H320 Causes eye irritation. Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

Causes skin and eye irritation.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Wear protective gloves.

Avoid release to the environment.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 1Reactivity = 0

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part A

 \cdot HMIS-ratings (scale 0 - 4)

HEALTH 1 Health = 1
FIRE 1 Fire = 1
PHYSICAL HAZARD $\boxed{0}$ Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
25085-99-8	Diglycidyl ether of bisphenol A homopolymer	75-100%	
64742-94-5	Solvent naphtha (petroleum), heavy arom.	≤5%	
84852-15-3	4-nonylphenol, branched	≤1%	
13463-67-7	titanium dioxide	≤1%	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Seek medical treatment.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part A

(Contd. of page 2)

- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage: cool and dry
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 4)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part A

(Contd. of page 3)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

 \cdot **Eye protection:** Wear appropriate eye protection to prevent eye contact.

α \mathbf{D}^{I}	• 1	1 1				
y Ph	UCICAL	and	\boldsymbol{c}	remical	nro	norties
	Bucal	unu	U	<i>temutu</i>	ט זע י	permes

General Information	
Appearance:	
Form:	Liquid
Color:	Grey
Odor:	Mild
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	>94 °C (>201 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure:	Not determined.
Density at 20 °C (68 °F):	1.14 g/cm³ (9.513 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	r); Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 5)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part A

(Contd. of page 4)

· Solvent content:

Organic solvents: 0.0 %

· Other information No further relevant information available.

· Volatile Organic Compounds: Not determined

10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

 Oral
 LD50
 5000 mg/kg (rat)

 Dermal
 LD50
 20000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye:

Strong irritant with the danger of severe eye injury.

Irritating effect.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

None of the ingredients is listed.

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)			
13463-67-7	titanium dioxide	2B	
7631-86-9	silicon dioxide, chemically prepared	3	
· NTP (National Toxicology Program)			
None of the ingredients is listed.			
· OSHA-Ca (Occupational Safety & Health Administration)			

(Contd. on page 6)

- US

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part A

(Contd. of page 5)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

· UN-Number

· DOT, ADR, ADN, IATA
· IMDG

Not Regulated
UN3082

· UN proper shipping name

· DOT, ADR, ADN, IATA Not Regulated

• IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin), MARINE POLLUTANT

(Contd. on page 7)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part A

	(Contd. of page 6
· Transport hazard class(es)	
· DOT, ADR, ADN, IATA · Class	Not Regulated
· IMDG	
· Class · Label	9 Miscellaneous dangerous substances and articles 9
· Packing group · DOT, ADR, IATA · IMDG	Not Regulated III
· Environmental hazards: · Marine pollutant:	No Symbol (fish and tree)
Special precautions for userEMS Number:Stowage Category	F-A,S-F A
· Transport in bulk according to Annex II of MARPOL73/ and the IBC Code	/78 Not applicable.
· Transport/Additional information:	
· DOT · Remarks:	Add "Marine Pollutant" to end of proper shipping name ij shipping in a bulk container (>119 gallons).
 ADR U.S. Domestic Ground Shipments: U.S. Domestic Ground Non-Bulk (119 gal or less per 	Same as listed for Standard Shipments above.
container) Shipments:	Same as listed for Standard Shipments above.
· Emergency Response Guide (ERG) Number:	Not determine
· UN "Model Regulation":	Not Regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

84852-15-3 4-nonylphenol, branched

≤1%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 8)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part A

(Contd. of page 7)

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7 titanium dioxide

A4

· MAK (German Maximum Workplace Concentration)

13463-67-7 titanium dioxide

3A

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

Causes skin and eye irritation.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Wear protective gloves.

Avoid release to the environment.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

(Contd. on page 9)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part A

(Contd. of page 8)

- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 03/17/2016 / 48
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Aquatic Acute 3: Hazardous to the aquatic environment - AcuteHazard, Category 3 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

- US

Tel: (800) 821-5846

Safety Data Sheet acc. to OSHA HCS

Printing date 03/17/2016 Reviewed on 03/17/2016

1 Identification

- · Product identifier
- · Trade name: Slow Set Bonding Agent Part B
- · Article number: 87-140440B
- · Application of the substance / the mixture
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Unitex®

Kansas city, MO 64120

3101 Gardner Fax: (816) 483-3149

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

· Information department: Environmental, Health, and Safety department.

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

3,6,9-triazaundecamethylenediamine

3,6-diazaoctanethylenediamin

2-(2-aminoethylamino)ethanol

2-piperazin-1-ylethylamine

· Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

(Contd. of page 1)

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

111-40-0 2,2'-iminodiethylamine

- · Identification number(s)
- · EC number: 203-865-4
- · Index number: 612-058-00-X
- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
112-57-2	3,6,9-triazaundecamethylenediamine	≤10%	
112-24-3	3,6-diazaoctanethylenediamin	≤10%	
111-41-1	2-(2-aminoethylamino)ethanol	≤1%	
140-31-8	2-piperazin-1-ylethylamine	≤1%	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms recieve medical treatment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

(Contd. of page 2)

· After swallowing:

Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

 $See \ Section \ 13 \ for \ disposal \ information.$

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

112-57-2 3,6,9-triazaundecamethylenediamine

WEEL Long-term value: 5 mg/m³

Skin; DSEN

112-24-3 3,6-diazaoctanethylenediamin

WEEL Long-term value: 6 mg/m³, 1 ppm Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Not determined.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

· pH-value:

Form: Liquid
Color: Amber

Odor: Distinctive

Odor threshold: Not determined.

· Change in condition

Melting point/Melting range: -39 °C (-38 °F)
Boiling point/Boiling range: Undetermined.

• Flash point: 94 °C (201 °F)

(Contd. on page 5)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

		(Contd. of page
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	335 °C (635 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	1 Vol %	
Upper:	10 Vol %	
Vapor pressure at 20 °C (68 °F):	0.49 hPa	
Density at 20 °C (68 °F):	0.9586 g/cm³ (8 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	e r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
Solids content:	100.0 %	
Other information	No further relevant information available.	
Volatile Organic Compounds:	Not determined	

10 Stability and reactivity

- · Reactivity No decomposition if stored and applied as directed.
- · Chemical stability No decomposition if stored and applied as directed
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Keep away from heat and sources of ignition.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

112-57-2 3,6,9-triazaundecamethylenediamine

Dermal LD50 660 mg/kg (rabbit)

(Contd. on page 6)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

112-24-3 3,6-diazaoctanethylenediamin

(Contd. of page 5)

LD50 | 2500 mg/kg (rat) Dermal LD50 805 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: May cause skin irritation.
- · on the eye: Strong caustic effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to Federal, State, and Local regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN2735
· UN proper shipping name · DOT, IATA · ADR · IMDG	Amines, liquid, corrosive, n.o.s. (Tetraethylenepentamine) 2735 Amines, liquid, corrosive, n.o.s. (Tetraethylenepentamine A M I N E S , L I Q U I D , C O R R O S I V E , N . O . (TETRAETHYLENEPENTAMINE), MARINE POLLUTANT
· Transport hazard class(es)	
$\cdot DOT$	
CORROSIVE	
· Class	8 Corrosive substances
· Label	8
· ADR, IATA	
· Class · Label	8 Corrosive substances 8
· Lavei · IMDG	0
· Class · Label	8 Corrosive substances 8

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

	(Contd. of page
· Environmental hazards:	
· Marine pollutant:	Yes
	Symbol (fish and tree)
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F- A , S - B
· Segregation groups	Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" acids.
· Transport in bulk according to Annex II of MARPOL73	/78
and the IBC Code	Not applicable.
· Transport/Additional information:	
\cdot DOT	
· Remarks:	Add "Marine Pollutant" to end of proper shipping name
	shipping in a bulk container (>119 gallons).
· ADR	
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· U.S. Domestic Ground Shipments:	Same as listed for Standard Shipments above.
· U.S. Domestic Ground Non-Bulk (119 gal or less per	
container) Shipments:	Same as listed for Standard Shipments above.
· Emergency Response Guide (ERG) Number:	Not determine
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S., 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to the State of California (Prop. 65) to cause cancer:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

(Contd. of page 8)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

3,6,9-triazaundecamethylenediamine

3,6-diazaoctanethylenediamin

2-(2-aminoethylamino)ethanol

2-piperazin-1-ylethylamine

· Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Do not breathe dusts or mists.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

- 119

Printing date 03/17/2016 Reviewed on 03/17/2016

Trade name: Slow Set Bonding Agent - Part B

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environmental, Health & Safety Department
- · Contact: Environmental, Health & Safety Manager
- · Date of preparation / last revision 03/17/2016 / 42
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

US